



UL Product iQ
 UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

NOW AVAILABLE

▶ LEARN MORE

**QMFZ2.E170540
 Plastics - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Plastics - Component

[See General Information for Plastics - Component](#)

DOMO ENGINEERING PLASTICS ITALY SPA
 VIA LINFANO 18
 38062 ARCO, TN ITALY

E170540

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
Polyamide 6 (PA6), "DOMAMID", furnished as pellets.											
6 G30 (d)	ALL	0.75	HB	5	-	65	65	65	-	-	-
		1.5	HB	4	-	65	65	65			
		3.0	HB	4	-	65	65	65			
6FC (d), 6 (d), 6 101 (d), S 6 (d), 6FC (d), 6AV (d), 6AV1 (d), 6S (d)											
	ALL	0.80	V-2	-	-	65	65	65	-	-	-
6G(a)H1 (d), 6G(a)H											
	ALL	0.75	-	4	0	130	80	125	0	6	0
		1.5	HB	3	0	130	85	130			
		3.0	HB	3	0	130	90	130			
6G35H1 (d), 6G35H	ALL	0.75	-	3	0	130	105	125	0	6	0
		1.5	HB	2	0	130	115	130			
		3.0	HB	2	0	130	115	130			
6IK2 (d), 6STC2	NC	0.8	HB	4	0	65	65	65	-	-	-
		3.2	HB	3	0	65	65	65			
6LV (d), 6 AF (d)	ALL	0.75	V-2	-	-	65	65	65	-	-	0
		1.5	V-2	-	-	65	65	65			
		3.0	V-2	-	-	65	65	65			
6LVGT85 (d)(f1), 6AFIE (d)(f1)											
	NC, BK	0.8	V-2	4	2	120	65	90	-	-	-
		1.0	V-2	4	2	120	65	90			
		1.8	V-2	4	1	120	65	90			
		3.0	V-2	4	1	120	65	90			
		3.2	V-2	2	0	120	65	90			
6LVGT85 (d), 6AFIE (d)											
	ALL	0.4	V-2	4	2	65	65	65	-	-	-
		0.75	V-2	4	2	120	65	90			
		1.0	V-2	4	2	120	65	90			

		1.8	V-2	4	1	120	65	90			
		3.0	V-2	4	1	120	65	90			
		3.2	V-2	2	0	120	65	90			
FR 6G(b)V0E (d), 6 G (b) V0EF (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 6G(h)GT96M(d)											
	ALL	0.75	V-2	-	-	65	65	65	-	-	-
		3.0	V-2	-	-	65	65	65			
FR 6G10V0E (d), 6 G10 V0EF (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 6G35V0E (d), 6 G35 V0EF (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 6V0M (d), 6V0M (d)											
	ALL	1.5	V-0	-	-	65	65	65	-	-	-
FR 6V0M1 (d), 6V0M1 (d)											
	ALL	0.8	V-0	-	-	65	65	65	-	-	-
		3.2	V-0	-	-	65	65	65			
Polyamide 66 (PA66), "DOMAMID", furnished as pellets.											
66 (d), 66SN (d)											
	ALL	0.80	V-2	-	-	65	65	65	-	-	-
66G(a)H1 (d), 66G(a)H											
	ALL	0.75	-	4	0	110	90	115	1	6	0
		1.5	HB	4	0	110	100	120			
		3.0	HB	3	0	110	100	125			
66G12IK1 (d), 66G12ST1X											
	NC, BK	0.8	HB	-	-	65	65	65	-	-	-
66G12IK1H2 (d) ,66 G12ST1X H2											
	ALL	0.8	-	-	-	65	65	65	-	-	-
66G25FC (d), 66G25FC											
	ALL	0.8	HB	-	-	65	65	65	-	-	-
		1.5	HB	-	-	65	65	65			
		3.0	HB	-	-	65	65	65			
66G35H1 (d), 66G35H											
	ALL	0.75	-	4	0	110	105	120	1	6	0
		1.5	HB	3	0	110	115	125			
		3.0	HB	3	0	110	115	125			
66G40H1 (d), 66G40H											
	NC	0.75	HB	-	-	65	65	65	-	-	-
FR 66G(b)V0E (d), 66 G(b) V0EF (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 66G10V0E (d), 66 G10 V0EF (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 66G20V0AH1 (d), 66G20V0AH (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 66G25V0AH1 (d), 66G25V0AH (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 66G25V0P1 (d), 66G25V0P (d)											
	NC, BK	0.75	V-0	-	-	130	65	65	-	-	-
FR 66G25V0P1A (d), 66G25V0P 1001A											
	NC, BK	0.8	V-0	-	-	65	65	65	-	-	-
		3.0	V-0	-	-	65	65	65			

FR 66G35V0E (d), 66 G35 V0EF (d)											
	ALL	0.75	V-0	-	-	65	65	65	-	-	-
FR 66G35V0P1 (d), 66G35V0P (d)											
	NC, BK	0.75	V-0	-	-	65	65	65	-	-	-
FR 66V0A (d), 66V0A (d)											
	ALL	0.8	V-0	-	-	65	65	65	-	-	-
		3.0	V-0	-	-	65	65	65			
Polyamide 66/6 (PA66/6), "DOMAMID", furnished as pellets.											
FR 66/6 V0M (d), 66/6 V0M (d)											
	ALL	0.40	V-0	-	-	130	90	100	-	-	0
		0.75	V-0	-	-	130	90	100			
		1.5	V-0	-	-	130	90	100			
		3.0	V-0	-	-	130	90	100			

- (a) - indicates one or two digit number from 6 to 34 denoting glass content
- (b) - indicates a two digit number indicating the glass fiber content from 11 to 34 percent
- (d) - optional alphanumeric code (2 to 12 digits/letter) denoting color
- (f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.
- (h) - indicates a two digit number indicating the glass fiber content from 15 to 30 percent

DOMAMID

Marking: Company name or trademark and material designation on container, wrapper or finished part.
Last Updated on 2018-03-02

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".