TECHNYL® PROTECT

Flame retardants

Comprehensive and customized range of flame- retardant products, based on PA6, PA66, co-polymer PA66.6 and special blends, keeping people and equipment safe from the spread of fire.



Fire Resistance

MAIN BENEFITS

Performance

- Class-leading fire protection and electrical performance
- Outdoor application suitable for some grades
- Fully colorable, customizable and laser markable

Processing

- Easy molding
- Reduced production cost
- Reduced corrosion of injection tools

MARKETS



HOME APPLIANCES



AUTOMOTIVE



BUILDING & CONSTRUCTION



ELECTRICAL & ELECTRONICS



MANAGEMENT

INDUSTRY-LEADING CERTIFICATIONS



Fire rating class: UL 94 V0, V1 or V2 depending on grade Yellow cards available, including RTI



Certified under EN 45545 Railway standard

R o H S + Compliance with EU environmental waste management directives and WEEE2 2002/96/CE

KEY APPLICATIONS









junction box solar



terminal block & connectivity system



TECHNYL' PROTECT

Flame retardants

PROOF POINTS

Fire


- UL certified materials with yellow cards all colors available
- GWFI 960°C 0.8mm
- GWIT from 775°C and higher, thickness down to 0.4mm

Electrical performance

- RTI available depending on grades, up to 150°C for electrical RTI
- CTI up to 600V and IPTI available on some grades

General performance

- UL f1 rating for specific grades for outdoor requirements
- UL MB approved for specific grades



unfilled

glass reinforced

KEY PRODUCTS

	BROMINATED PA66 – PA6	RED PHOSPHORUS PA66	HFFR PA6	HFFR PA66
FILLED	TECHNYL® PROTECT A 30H1 V30	TECHNYL® PROTECT A 20 V25	TECHNYL® PROTECT C 52G4 MZ25	TECHNYL® PROTECT A 60G1 V25
	TECHNYL® PROTECT C 30H1 V30	TECHNYL® PROTECT A 20 V35	TECHNYL® PROTECT C 52G1 MX25	TECHNYL® PROTECT A 60G1 V30
		TECHNYL® PROTECT AT 20 V25	TECHNYL® PROTECT C 52G2 MV25	TECHNYL® PROTECT A 60X1 V25
		TECHNYL® PROTECT A 21T3 V25	TECHNYL® PROTECT C 52G1 V20	TECHNYL® PROTECT A 60X1 V30
		TECHNYL® PROTECT A 21T4 V25 BK (new)	TECHNYL® PROTECT C 52G1 V25	
			TECHNYL® PROTECT C 52G1 V30	
			TECHNYL® PROTECT C 52G2 V20	
UNFILLED			TECHNYL® PROTECT C 52G3 V25	
	TECHNYL® PROTECT A 30G1		TECHNYL® PROTECT C 50H2	TECHNYL® PROTECT A 50H1
			TECHNYL® PROTECT C 50H3	TECHNYL® PROTECT A 50X1
			TECHNYL® PROTECT C 52G2	TECHNYL® PROTECT A 50X2
				TECHNYL® PROTECT A 50X3
				TECHNYL® PROTECT B 50H1

TECHNYL® IS EXCLUSIVELY PRODUCED AND COMMERCIALIZED BY DOMO WORLDWIDE







